



Parts List

Connectors

- A 8 pieces
- B 2 pieces
- C 2 pieces
- D 4 pieces

Poles

- E (7') 8 pieces
- F (8') 5 pieces
- G (5') 5 pieces
- H (3') 6 pieces

Tarpaulin

2 pieces 7 1/2' X 6 3/4'

Cable Ties

1 bag

Figure 1. Har Shalom Men's Club Home Sukkah

## Har Shalom Men's Club Home Sukkah Kit Assembly Instructions

Mazel Tov for performing the mitzvah of building a Sukkah! Follow these instructions and you will have your Sukkah assembled in a minimum of time. Once, assembled, all you have to do is put s'chach on the roof and decorate the Sukkah. Assembly requires two people. All parts are marked as shown in Figure 1. Before starting assembly, check the quantity of parts against the list in Figure 1 and read the instructions thoroughly. Contact the Men's Club if you have any questions.

### Tools Needed:

1. Connections are friction fit. However, a mallet or equivalent piece of wood should be used to tap the parts so that they fit snugly.
2. A small ladder is suggested for safety reasons
3. Use a pair of scissors or wire cutters to cut the cable ties during disassembly

### Instructions:

1. Assemble the top assembly using three F pipes, four G pipes, four A connectors in the corners and two B connectors in the middle.
2. Assemble the bottom assembly using two F pipes, four G pipes, four A connectors in the corners and two C connectors in the middle.
3. Place six E pipes vertically into the connectors on the top assembly.
4. Carefully turn over the top assembly with the vertical pipes in place and align all six connectors in the bottom assembly with the vertical pipes and gently, and firmly, tap them into place with a mallet or equivalent piece of wood.
5. Join three H pipes with two D connectors to make a long pole. Make a second one the same way. Place the two long pipes on the top assembly as shown in Figure 1 so that the five cross pipes on the top are evenly spaced. Tie the two long pipes to the Top Assembly using the cable ties provided.
6. Starting at the corner next to the Sukkah doorway, loosely tie the tarpaulin to the top assembly poles using the cable ties. If you do not overly tighten the cable ties they may be left on the tarpaulin and re used in following years. Wrap tarpaulin around the Sukkah as far as it goes. The doorway may be on either the long or short side, as you desire. Connect the second tarpaulin in the same manner starting at the other side of the doorway. The two tarpaulins will overlap about a foot or more. Position the tarpaulin evenly and adjust the ties. If cable ties are not tightened too tightly they may be kept in place at disassembly and re used in subsequent years.
7. Disassembly. Take down the Sukkah in the reverse order that you assembled it. The ties may be left in place on the tarpaulin and re used if they were not tightened too tightly, or you may cut the cable ties. There are enough ties to last for two years. Put loose parts in the bag provided and store with the pipes, tied together, in a safe place.